CIMPLASTA
since 1954

AQUASTOP

Usage

It is a product which is used to prevent flooding in case of a malfunction. It consists of a mechanic valve, an inner hose (PVC inlet hose) and a protective outer hose set. When a water leak happens in the inlet hose, the water is accumulated by the protective hose and it reaches the blockage mechanism in the valve so that the valve is closed and flooding is prevented. The mechanism works without any need of an electrical power supply.

Features

- Magnetic system without sponges or electrical parts
- 100% tested (reversible) so PPM=0
- Reliable (mechanical parts only in movement)
- Cheaper than actual systems on the market
- Useful for appliances (washing machines, dish washers) but also for main sectors (coffee machines, industrial washing machines, generally what employ water supply)

Material	**PP, PVC, NBR, EPDM, PA 66**
Water Supply Pressure	**0,2-10 bar**
Cold Water Working Temperature	**5°C < t < 60°C**
Hot Water Working Temperature	**5°C < t < 90°C**
Ambient Operating Temperature	**5°C < t < 70°C**
Hose Inner & Outer Diameter	**9 x 13mm / 10 x 15mm**
Leak Tightness Pressure	**6 bar**
Flow Rate	**10 L/min**
Thread of Nut	**¾ ISO 228, ASME ¾ 11.5 NH**
VDE Number	
Standard	**EN 61770**
Burst Pressure	**60 bar**



CIMPLASTA SRL – 6, VIA CASCINA NUOVA – I21029 VERGIATE (VA)
PHONE +39 0331946136 - EMAIL CIMPLASTA@CIMPLASTA.IT